## This Page Is Inserted by IFW Operations and is not a part of the Official Record

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Problem Image Mailbox.

		1			
<i>t</i>	÷	•			
				A Marian Company of the Company of t	
				•	
	•		•		
	,		1		
			d.		
•		en e			
			e e		
•					
					Nd
•					
•	*			· · · · · · · · · · · · · · · · · · ·	
		en e			
	÷	A			
- - بو					
, -		<u></u>	en e		- <del></del>
: 					
- '		and Section 1995			<del>N</del> a
	· · · · · · · · · · · · · · · · · · ·		· .		
, v			i de la companya de l		4
			en e		e e e e e e e e e e e e e e e e e e e



## THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE: PRESENTS: SHALL COME: UNITED STATES DEPARTMENT OF COMMERCE

**United States Patent and Trademark Office** 

**September 16, 2000** 

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/141,424 FILING DATE: June 29, 1999

REC'D 1 3 OCT 2000

# PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)



By Authority of the COMMISSIONER OF PATENTS AND TRADEMARKS

M. LEE
Certifying Officer

Docket Number:

086/00672

PROVISIONAL

PLICATION FOR PATENT CO

SHEET (Small Entity)

			INVEN	TOR(S)/API	LICANTIS			
Given Namo (first a	nd middle [if any])	Fam	ily Name or			lence /Ch	Named although	
Thodoros		TOPALOGLOU		Residence (City and either State or Foreign Country Menio Park, CA			us or Foreign Country)	
Additional	inventors are b	eing name	d on page	e 2 attache	d hereto		····	
					280 characters			
BIOLOGICAL DAT	TA PROCESSIN	IG ·						
irect all correspon	dence to:		CORRES	PONDENCE	ADDRESS			
Customer Num						,	Place Custom Bar Code Li	er Number abel here
Firm or Individual Nam	e William H. D	Hppert, Esc						
ddress	Cowan, Lieb							
ddress	1193 Ауепце							
Ity	New York	_		State	INY		770	lanea-
ountry	U.S.A.			Telephone		200	ZIP Fax	10036-6799 (212) 575-0671
		ENCLOSE	APPLIC/	ATION PART	S (check all t			(212) 919-09/1
Specification	Number	of Pages	22	7	Small Enti			
Drawing(s)	Number	of Sheets			Other (spe	atore [	Appendix:A (	pps 18-22 of
METHOD C	F PAYMENT OF	FILING FE	ES FOR T	HIS PROVE	SIGNAL APPI	E	pecification)	
A check or m	oney order is en	Noned to an					TUR PATE	NT (check one) FILING FEE
								AMOUNT
	sloner is hereby a expayment to Dep	DOZIC ACCOUNT	nt Number	-		419 *		\$450.00
invention was made t	y an agency of the	United States	Governmer	t or under a c	ontract with an ag	ency of th	e United States	\$150.00
Ī	•							recommend.
Yes, the name of t	the U.S. Governmen	nt agency and	the Govern	ment contract	number are:	_		
spectfully submitt	ed,							
NATURE /	aul 3	Fens	len		Date	,	06/	29/1999
ED or PRINTED	NAME Paul	FENSTER			REG	ISTRA	TION NO.	
					(if at	proprie	te)	33,877

A PROVISIONAL APPLICATION FOR PATENT SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, DC 20231

Page 1 of 2 |

P19SMALL/REV04

Express Mail Label No. e1007	668939us	
I hereby certify that this pa with the U.S. Postal Service to Addressee" service under 3 indicated above and is address Patents and Trademarks, Washin	7 CFR 1.10 on	Post Office the date
Jose Ortiz	Stree	Orti:
Name of Person Mailing	Si	gnature
		٠.,

EXPRESS MAIL CERTIFICATE 37 CFR 1.10

June 29, 1999

Date of Deposit \_

comment in the comment

5

10



#### FIELD OF THE INVENTION

The present invention relates to automated database searching and in particular to automated access to biological databases.

#### **BACKGROUND OF THE INVENTION**

One of the tasks performed in biological research is comparison of newly discovered biological data with data stored in databases. Over two hundred public biological databases are available around the world, many on the Internet. In general, databases include a plurality of records which have the form of an object class. The object class is formed of a plurality of fields, often in a hierarchy in which an object classe includes one or more sub-object classes which in turn may include sub-sub object classes. The records may represent, for example, gene sequences and may have fields which include various data about the sequences, such as their length, origin and a view of the sequence. Information is extracted from databases by querying a management system associated with the database. A simple query includes a request to display one or more fields of records which fulfill a certain criteria.

The existing databases have different organization methodologies, e.g., different fields in each record and different query schemes. In order to access these databases with ease, an Object Protocol Model (OPM) suite of tools was developed. An OPM processor mediates between a user and databases associated with the OPM suite. A common organization methodology is used to represent the data in all the databases accessed via the OPM processor. Queries addressed to databases via the OPM processor-are-provided, by a user to the OPM processor, in a structured form expressed in accordance with the common organization methodology. The OPM processor translates the queries from the structured OPM form to query forms compatible with the management systems of the specific databases to which the queries are addressed. The results from the specific databases are returned to the OPM processor which translates the results back to the organization methodology of the OPM suite. Not only does the OPM suite allow a user to access a plurality of different databases in different forms, it also allows the user to access a plurality of databases using a single query. For example, a complex query may request to display the records from a first database which have a gene length greater than of corresponding records of a second database which represent the same organism.

The use of a common organization methodology across databases allows using special tools for more easily generating queries and/or performing more complex queries. For example,

5

10

a graphic user interface (GUI) of the OPM suite allows the user to prepare a query in a structured manner.

Some of the forms of biological data are complex data structures, such as gene sequences, which require special procedures for manipulation, for example, for performing comparisons. Homology search engines, such as BLAST, are used to compare gene sequences. When a user wants to compare, for example, all the gene sequences classified in a certain month to one or more groups of gene sequences, the user retrieves all the desired classified gene sequences using OPM. Then, the user passes the retrieved data to a homology sequence server which performs the sequence comparison.

#### SUMMARY OF THE INVENTION

One object of some preferred embodiments of the invention is to provide a method for accessing data manipulation servers using a structured query format used to query databases. Preferably, the accessing of manipulation servers is integrated with the accessing of database information, for example by manipulating the results of the data access and/or by using the results of the data manipulation as data to be accessed or for restricting queries.

One aspect of some preferred embodiments of the present invention relates to a multi-database query system which receives queries which relate to both database and data manipulation servers, such as homology search engines. The queries relate to the data manipulation servers as if they are database servers, allowing use of any tool of the multi-database query system developed for database queries, on queries which access data manipulation servers. Such tools include, for example, database linking tools, graphic query preparation tools and query optimization tools. By relating to databases and data manipulation servers from a single query, the data manipulation server may process results from the database as they are provided before the database runs through all its records. Alternatively or additionally, the results of a data manipulation step may be further queried. Thus, the response time required for a complex query may be substantially reduced. Alternatively or additionally, the amount of traffic on a network may be reduced and/or better spread out in time. Also, complex operations may require less of a user intervention.

In some preferred embodiments of the present invention, the input to and/or output from of the data manipulation servers are modeled by structured objects. The modeled input objects may result from processing other sections of the query. The modeled output objects may be further processed by other sections of the query or even further manipulated by other (or the same) manipulation servers.

10

In a preference embodiment of the present invention, each data manipulation server associated with the query system has a translation server which mediates between the data manipulation server and the query system. The translation server receives commands from the server in a structured query form used by the query system and translates the commands to a form in which the data manipulation server receives commands. The translation server preferably also receives results from the data manipulation server and presents the results to the query system in objects organized according to structured object classes used by the query system.

There is thus provided in accordance with a preferred embodiment of the invention, a multidatabase query system which queries a plurality of databases and servers, comprising:

an input which receives queries in a structured form; and

a translation server which translates at least a part of a received query into commands recognized by a data manipulation server. Preferably, the system comprises a processor which parses the received query into parts according to the databases and servers to which they relate. Alternatively or additionally, the structured form comprises a form used to query databases. Alternatively or additionally, the input receives a query which relates to at least one database and at least one data manipulation server. Alternatively or additionally, the translation server models results from the data manipulation server into database objects. Alternatively or additionally, the data manipulation server which receives input from a least two different sources. Preferably, the data manipulation server comprises a homology comparison engine.

There is also provided in accordance with a preferred embodiment of the invention, a method of accessing a data manipulation server from a multi-database query system, comprising:

providing the query system with a query which includes a first directive assigning a value to at least one field of an input object associated with the data manipulation server and a second directive which determines a value of at least one field of an output object associated with the data manipulation server; and

invoking the data manipulation server responsive to the second directive. Preferably, providing the query comprises preparing the query using a graphical interface designed for querying structured databases. Alternatively or additionally, the data manipulation server comprises a homology engine.

5

10

There is also provided in accordance with a preferred embodiment of the invention, a method of performing a database search using a multi-database query system, comprising:

providing the query system with a query which includes at least one directive related to a database and at least one directive related to a data manipulation server, wherein the directives are stated in an identical structural format;

translating the directives into commands recognized by the database and the data manipulation server; and

submitting the commands respectively to the data manipulation server and to the database. Preferably, the data manipulation server comprises a homology comparison engine. Alternatively or additionally, translating the directives comprises identifying, by a query processor, the directives directed to the database and the directives directed to the data manipulation server. Preferably, translating the directives comprises passing the directives to translation servers associated with the database or data manipulation server to which the directives are directed. Alternatively or additionally, the method comprises determining an order for the directives to be processed in and submitting the translated directives to the data manipulation server and to the database according to the determined order.

In a preferred embodiment of the invention, the method comprises receiving results from said submission and translating the results into structured objects. Preferably, translating the results into structured objects comprises translating the results to structured objects related to the directives.

Alternatively or additionally, providing a query comprises providing a query in an Object Protocol Model (OPM)-like language.

#### BRIEF DESCRIPTION OF FIGURES

The invention will be more clearly understood by reference to the following description of preferred embodiments thereof in conjunction with the figures, in which:

Fig. 1 is a schematic illustration of a multi-database query system, in accordance with a preferred embodiment of the invention; and

Fig. 2 is a flowchart of the actions performed by the multi-database query system of Fig. 1, in accordance with a preferred embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a schematic illustration of a multi-database query system 20, in accordance with a preferred embodiment of the invention. System 20 mediates between an end-user 22, and a plurality of service providers which include databases 24 and one or more data

5

10

manipulation servers, such as a homology search engine 26. Error detection processes are another example of data manipulation servers. Engine 26 is a data manipulation server in that it provides processing services and is not primarily used for storing and providing information. Preferably, engine 26 does not store information and a user requesting processing services must provide the information to be processed or must provide a link to a database or file containing the information. Data manipulation servers may receive a single input of data, e.g., error detection processes which receive a single sequence, or a plurality of inputs, c.g., homology engines which compare sequences from two different sources. One of the objects of some preferred embodiments of the invention is to allow end-user 22 to relate to homology engine 26 and/or to other data manipulation servers as if they were databases 24.

Databases 24 may be organized differently from each other and are not generally controllable by a supervisor of system 20. End user 22 provides system 20 with queries in a query-language of system 20, preferably a structured query language, such as OPM. Preferably, a single query may be directed to more than one service provider. For example, a single query may be directed to a plurality of databases 24 and to homology engine 26.

Preferably, system 20 comprises a graphical user interface 28 which receives queries in a graphical form and translates them into the system's query language. Alternatively or additionally, system 20 comprises a command-line interface 30 which receives commands from end-user 22 directly in the system's query language or possibly using natural language. Further alternatively or additionally, system 20 comprises a remote-unit interface 32 which receives queries from remote computer units.

System 20 further comprises a multi-database query processor 34 which receives queries from interfaces 28, 30 and/or 32 and processes them; as described bereinbelow. Preferably, query processor 34 and interfaces 28, 30 and/or 32 are implemented in software on a single computer 36 accessible to end-user 22. However, a distributed configuration can also be used.

Preferably, system 20 further comprises, for each database 24, an OPM translation server 38 that mediates between processor 34 and the respective service provider. Preferably, translation servers 38 translate queries from the query language of system 20 into query languages supported by the respective database 24. Further preferably, translation servers 38 translate query results received from the databases 24 into the structural object classes of system 20.

10

In a similar manner, system 20 preferably comprises an OPM translation server 42 which mediates between processor 34 and homology engine 26. Translation server 42 preferably translates query portions from the query language of system 20 into commands supported by homology engine 26. That is, the OPM language allows, in accordance with preferred embodiments of the invention, phrasing queries that access homology engine 26 as a database. Translation server 42 translates query directives, such as limitations, into commands to be performed by homology engine 26. In addition, translation server 42 preferably translates the output from homology engine 26 into structural objects, in accordance with the query language used by system 20. An exemplary structural definition of objects used to access a homology engine from the OPM suite is described in appendix A. The structural definition of appendix A is written in a language used to define OPM objects, described for example in Chen, I.A.; Kosky, A.S.; Markowitz, V.M.; Szeto, B.; and Topaloglou, T., 1998. "Advanced Query Mechanisms for Biological Databases" in Proceedings of the 6th International Conference on Intelligent systems for Molecular biology (ISMB'98), the disclosure of which is incorporated herein by reference.

Alternatively or additionally, a single translation server 38 may be used for more than one service provider. Alternatively or additionally, OPM processor 34 performs some or all of the translation tasks of translation servers 38 and 42. Preferably, OPM servers 38 and 42 are situated on the same computer as their respective service providers 24 and 26. Alternatively, OPM servers 38 and 42 are located on computers proximal to their respective service providers 24 and 26, although translation servers may be located substantially anywhere.

Preferably, a multi-database directory 40 is used by processor 34 to determine to which service provider 24 and 26, the portions of a query are directed. Directory 40 preferably summarizes the contents, organization methodologies and capabilities of databases 24 and engines 26. In a preferred embodiment, a single directory is used for a plurality of query processors 34, such that adding additional service providers to system 20 requires only preparing a respective OPM server for the additional service providers and updating directory 40, while no changes are needed in processors 34.

In a preferred embodiment of the present invention, the various components of system 20 interact using a distributed-object technology, such as, the Common Object Request Broker Architecture (CORBA) which is described, for example, in the Web Site of the "Object Management Group" (OMG) at www.omg.org and was available on June 27, 1999. The disclosure of this web site is incorporated herein by reference. Preferably, a plurality of

10

25

30

different CORBALL terfaces are used in system 20 for different typ s of interactions between the components of system 20. In one example, a first CORBA interface is used for programming and a second interface is used for object transfer and/or sharing. Preferably, remote-unit interface 32 also comprises a CORBA interface.

Alternatively or additionally, other distributed-object technologies, such as, Microsoft's Component Object Model (COM) or the UNIX environment Remote procedure call (RPC), may be used to allow remote and/or non-remote components of system 20 to interact. Further alternatively or additionally, system 20 may be implemented in its entirety by a single process and/or on a single processor.

		Table 1				
	(1)	SELECT	l = r.fragId, a =h.accessor			
	(2)	FROM	r in local:Fragments			
(n	(3)		bc in blast:Blast_Call			
145	(4)		bo in bc.output			
Ė	(5)		h = bo.summary.sequence			
i de	(6)	WHERE	r.finished = "today" and			
Ē	(7)		bc.querySeq = r.sequence and			
Ë	(8)		bc.command = "blastn" and			
20	(9)		bc:dataSource = "dbEST" and			
(f)	(10)		h.length > 300			
lŲ .D						
	Table 1 illustrates a sample query received					
28, 30 and 32. The query in table 1 is writtened						

Table 1 illustrates a sample query received by query processor 34 from any of interfaces 28, 30 and 32. The query invable 1 is written according to the OPM query language described, for example, in the ISMB'98 publication referenced hereinabove. This OPM query language allows accessing a plurality of databases, 24 from a single query. The query of table 1 relates to both a database 24 and an homology engine 26, the homology engine being accessed as if it were a database.

The query in table 1 is built of three sections. A first section labeled SELECT states the fields which are to appear in the output generated responsive to the query. In table 1 these fields are a "fragId" field of a variable r, and an "accessor" field of a variable h (the variables r and h are defined in the second section). A second section, labeled WHERE, defines the

25

30

10

variables mentioned in the query by stating the database object classes to which they relate. That is, the second section states which objects are candidates for fulfilling the query.

In table 1, the variable r, for example, corresponds to a "Fragments" object class in a database named "local". In the same way, a dummy variable "bc" corresponds to an object class named "Blast\_Call" in a pseudo database "blast". However, unlike variable r which represents an actual field of data in a database 24, variable "bc" does not represent any such field, and a database "blast" does not actually exist.

Rather, when the "blast" database is referred to in a query, processor 34 refers to homology engine 26. Translation server 42 preferably performs any required translations to the input and output of homology engine 26, such that the homology engine appears to processor 34 as a database. Preferably, the entire interface with homology engine 26 is structured in a single translation object, for example, in accordance with the "Blast\_Call" object class in table 1, which is defined in appendix A. The translation object includes the input to and output from homology engine 26. For example, the "Blast\_Call" object class has fields which relate to the commands to engine 26, such as, a "command" field which states the type of command performed by engine 26, a "querySeq" field which states an input sequence to be compared by the engine and a "dataSource" field which states a database of sequences to which the input sequence is compared. In addition, the "Blast\_Call" object class has an "output" field into which the output from homology engine 26 is preferably structurally stored. In the query of table 1, a dummy variable, "bo", refers to the sub-object "output", thus simplifying the query statements.

When a query relates to an action, such as a search or a filter to be performed in a pseudo database, processor 34 first has the respective engine 26 perform any required commands to fill up the output fields of the object representing the pseudo database, e.g., "Blast\_Call", and only then the search is performed. Alternatively or additionally, as the output records become available from homology engine 26 they are sent for further processing. In some cases, the records can be processed even before all the fields are available from engine 26. One example of a query optimization as applied to data manipulation servers is that the query translator instructs the engine to prepare only those result fields which are actually required for further processing or display. Another example of optimization is allowing some of the fields to be provided at a later time than other fields. Modifying the order of generation of fields, even between records, may be useful if the some fields are required for further data manipulation or for a querying against a slow database and are thus time critical. For some

types of data manufation, it may even be useful to start the manipulation with only part of the fields and then repeat the manipulation with the rest of the fields. One example where it is useful to start manipulating before all the fields are available is where the manipulation can be carried out, at least to some extent, without the field or where the value of the field or the rang of possible values of the field can be known. Thus, for example, a DNA homology can be failed based on both of the strands not matching, even before it is known which strand needs to be matched. Once the strand information is available, the group of accepted matches can be further limited using that information.

Thus, system 20 can have different parts of a query evaluated in parallel, in particular, time consuming parts performed by data manipulation servers. For example, homology engine 26 may begin to operate as records from another part of a query become available, and/or the output from engine 26 may be processed as it is provided, without waiting for all the results. This parallelism is possible because homology engine 26 is accessed from within the query. An advantage of some embodiments of the invention is the savings in response time and in communication and CPU resources of complex queries due to this parallelism.

In some cases, such parallel processing of data manipulation may require the data manipulation server or the data manipulation program itself to be modified to take the timing information into account. In one example, a blast server may associate the actual partial information used with a result record set, so that it can further limit the search results after the fact.

A third-section of the query, labeled WHERE, states the conditions to be fulfilled by those objects selected by the query. In table 1 these conditions include that a field named "finished" of the variable r must have a value "today", a field "query. Seq" of the variable be must have a value equal to the value of the field "sequence" of variable r, etc. In this section, the conditions on database objects and on pseudo database objects are preferably stated substantially in the same way.

Fig. 2 is a flowchart of the actions performed in processing a query by system 20, in accordance with a preferred embodiment of the present invention. Upon receiving a query, such as the query in table 1, processor 34 divides (60) the query into parts which are performed by the various service providers 24 and 26. Processor 34 preferably determines, for example using methods known in the art, to which service provider each line in the query is directed. Preferably, the determination is performed by reference to directory 40. In the query of table 1, processor 34 determines from the second line that variable r is to be searched in the database 24

30

5

10

named "local". From the third line it is determined that variable be is to be "searched" in engine 26 named "blast". Therefore, lines 2 and 6 of the query are directed to the database "local" and lines 3, 7, 8 and 9 are directed to homology engine 26. Lines 1, 4, 5 and 10 do not refer to any database and therefore they are preferably processed by processor 34.

Processor 34 then preferably determines (62) the cross-dependence of the parts of the query, i.e., which parts require data from other parts and therefore must receive the data from the other parts before they are performed. In table 1, it is determined from the line 7 that the query part directed to homology engine 26 requires output from another query part.

Thereafter, processor 34 sends (64) to OPM translation servers 38 and/or 42 a first round of query parts belonging to their respective service providers 24 and 26. The query parts sent in the first round are those which do not require results from other queries. In table 1, the part relating to variable r, i.e., lines 2 and 6, are sent to the OPM server 38 of database "local". These lines designate a query for all the Fragment objects in the database which have a value "today" in their "finished" field. The OPM server translates (66) the received query part into a language recognized by database "local". The translated query part is passed to the database 24 which processes (68) the query and returns (70) the results of the query to the respective OPM server 38. The OPM server 38 translates (72) the results received from the database 24 into the OPM result format and passes the translated results to processor 34.

If (74) the query includes additional query parts which were not performed yet, e.g., query parts dependent on results from other queries, steps 64, 66, 68, 70 and 72 are repeated for the additional query parts. In the example of table 1, the query part formed of lines 3, 7, 8 and 9 is passed to the translation server 42 of homology engine 26. The translation server 42 translates (66) the query part into commands performed by homology engine 26. For each sequence of variable r in the output of database "local", translation server 42 sends a "blastn" command to engine 26 to perform a homology comparison between the sequence and the database "dbEST". The results received from engine 26 are preferably summarized (72) by translation server 42 in the "output" field of the "Blast\_Call" object.

In some preferred embodiments of the present invention, system 20 begins a second round of processing query parts before a first round on which the second round depends, is finished. Rather, as the first round provides records as results, the second round can manipulate them.

Once all the query parts were handled by their respective service providers 24 and 26, processor 34 performs (76) any remaining operations in the queries and provides (78) the user

10

with the results required in the SELECT section of the query. In the example of table 1, processor 34 performs the comparison in line 10 of the query. Variable h refers to the field "sequence" of the sub-object "summary" of the object "output", which represents the results from the blast comparison. Sequences having a length greater than 300 are selected from the blast results. The user is then provided with the value of the "accessor" field of the variable h and with the value of the "fragId" field of the variable r, for all the objects which fulfill the query.

The above description has focused on BLAST as a homology method, however, other types of homology servers may also be used, for example BLASTX, BLASTN and BLASTP. Additionally, other types of data manipulation may be provided, for example, error correction, in which a sequence is corrected for various types of errors. Another type of data manipulation server is for example a server which guesses a ternary structure of a protein from its sequence, for example the number of alpha helixes or the protein's affinity to a certain DNA sequence. Alternatively to guessing the structure, the server may provide a grading facility which grades a list of provided sequences for affinity to the protein (or for similarity of their derived protein) or which selects those sequences which have a certain affinity.

As can be appreciated, some of these data manipulation servers require only one input record set while others, require more than one input record set. For example, a homology search can compare a first set of records against, records in a second database (fixed value) or against a second set of provided records. In some cases, three or more inputs may be provided, for example where a third record set includes a list of rules, which apply, when, comparing the two record sets. In some cases, all the record sets needs to be fully specified before the manipulation can be performed. In other cases, only one or possibly not even one, of the record sets needs to be fully specified before starting the manipulation. The considerations for optimizing and performing in parallel can be applied to the availability of record sets as well. In a preferred embodiment of the invention, the definitions of how the data manipulation server operates in the absence of data and/or the relative computation time for different tasks thereby are stored in directory 40, preferably along with other information useful for optimizing queries which include data manipulation.

An advantage of some of the above preferred embodiments is that it is possible to use substantially any tool developed for manipulation of databases to access data manipulation servers. For example, graphic interface 28 may be an interface developed solely for preparing queries for database servers, as described, for example, in Kosky, A.S., Chen, I.A., Markowitz,

V.M., and Szeto, E. "Exploring H terogeneous Biological Databases: Tools and Applications", Proceedings of the 6th International Conference on Extending Database Technology (EDBT'98), Lecture Notes in Computer Science, Vol. 1377, Springer-Verlag, 1998, pp. 499-513, the disclosure of which is incorporated herein by reference. A user may use this interface to prepare sophisticated queries which include access to data manipulation servers, such as homology search engines.

Likewise, optimization tools designed for database queries may be applied, in accordance with the above preferred embodiments, to queries which include reference to data manipulation servers. Such optimization is especially important for queries which reference data manipulation servers because usually these servers require substantially more processing time than databases.

Furthermore, the results of the queries are preferably provided in a single common format which allows use of a single standard output interface to display the results.

In addition, variables representing database and pseudo database objects may be linked together using methods for linking databases described, for example, in the EDBT'98 publication referenced hereinabove. These linking methods allow simpler statement of queries and hence more transparency to the user who does not need to know the structure of the various servers used.

Although the above described embodiments refer to queries which relate to data manipulation servers as to databases, some embodiments of the invention relate to queries which include commands to be performed by data manipulation servers, not necessarily in the same manner in which databases are searched. For example, a query may include an explicit command to be carried out by a data manipulation server, e.g., homology engine 26. Such commands are referred to herein as application specific data type (ASDT) commands.

Table 2 shows a query similar to the query of table 1 in which homology engine 26 is activated using explicit commands written in a format acceptable by OPM processor 34. Line 6 in table 2 is a command to perform "blast" on the "sequence" fields of the possible values of variable r. The blast is performed against a database "dbEST". The results from performing the blast command appear in a variable b which is defined in line 3 of table 2.

30 <u>Table 2</u>

SELECT l=r.fragId, a=h.accessor

(2) FROM r in local:Fragments

(3) b in blast:Output

[Fi
∰5
=
Ę
2
Ę
U
1 100
20
ĮΠ
IJ
٠Ū
Ų

٠Đ

30

10

	(4)		h = bo.summary.sequence
	(5)	WHERE	r.finished = "today" and
	(6)		r.sequence.blast("dbEST") and
	<b>(7)</b>		b.query = r.sequence and
5	(8)		h.length > 300

In a preferred embodiment of the present invention, when processor 34 encounters an ASDT command, such as the "blast" command on line 6, it first checks with the database involved, i.e., the "local" database; whether the database supports the command in the specific syntax. Then, processor 34 consults directory 40 to determine a server which has the routine invoked by the command. Processor 34 passes the ASDT command, with whatever data objects to which the command relates, directly to the determined server. Alternatively, the command is passed through translation server 42. The output from the server is preferably passed to processor 34 in a structured form, as described above, so as to allow easy manipulation of the results. In this embodiment, processor 34 does not model homology engine 26 as a database 24, but does access the homology engine from within a complex query which accesses databases.

The ASDT commands do not necessarily appear in the WHERE section of the query. Table 3 shows a query in which a command appears in the SELECT section of the query. The command is processed after the query is evaluated, at a stage of presenting the results of the query.

hit	

- (1) SELECT x.gelld
- (2) x.image.crop(0,0,200,400).display().
- (3) FROM x in Gel
- 25 (4) WHERE 2 x.gelld = "gel=000111"

In table 3, an "image" field of the variables x which satisfy the query are passed to a routine "crop", which returns a piece of an image having specified coordinates. The results from the routine "crop" are passed to a routine "display" which displays the result in any desired manner.

The routines referenced by the ASDT commands may be evaluated by a data manipulation server as described above with reference to the blast command evaluated by homology engine 26. Alternatively or additionally, some routines may be situated within

10

processor 34 or in directory 40. The statement of the commands within a query rather than invoking the commands on the results received from a query, is simpler to the user. In addition, invoking the commands from within the query allows performing the command before the results are passed to end-user 22. In many cases this conserves substantial communication resources.

In some cases users accessing databases are frequently interested in attributes which may be extracted from the image of a complex data field, for example, a gel. Such attributes include, for example, the length of an image of the gel, its average intensity or specific lanes of the image. Therefore, some databases have redundant data fields which have values for these attributes. By using ASDT commands these redundant fields are not needed. The routines invoked by the ASDT commands may be stored in the database 24, on a separate data manipulation server, in directory 40 and/or in processor 34.

It is noted that the ASDT commands may be invoked implicitly as described above with reference to Fig. 2. For each command, a command data object is preferably defined which includes input and output fields of the command. An access to an output field of the object is translated by system 20 as an implicit invocation of the command.

It will be appreciated that the above described methods may be varied in many ways, including, changing the order of steps, and the exact implementation used. It should also be appreciated that the above described description of methods and apparatus are to be interpreted as including apparatus for carrying out the methods and methods of using the apparatus. Especially, the above methods should be interpreted to describe software for carrying out a complete method as described above, a part thereof or software which modifies an existing software to perform as described above. In addition, the scope of the invention includes such software stored in a computer readable media, such as a disk, stored in a memory or executing on a computer.

It is noted that the above described embodiments are given by way of example only, and the scope of the invention is limited only by the claims. When used in the following claims, the terms "comprise", "include", "have" and their conjugates mean "including but not limited to".

25

30

#### **CLAIMS**

1. A multi-database query system which queries a plurality of databases and servers, comprising:

an input which receives queries in a structured form; and

- a translation server which translates at least a part of a received query into commands recognized by a data manipulation server.
- A system according to claim 1, comprising a processor which parses the received query
   into parts according to the databases and servers to which they relate.
  - 3. A system according to claim 1, wherein the structured form comprises a form used to query databases.
  - 4. A system according to claim 1, wherein the input receives a query which relates to at least one database and at least one data manipulation server.
  - 5. A system according to claim 1, wherein the translation server models results from the data manipulation server into database objects.
  - 6. A system according to claim 1, wherein the data manipulation server comprises a server which receives input from a least two different sources.
  - 7. A system according to claim 6, wherein the data manipulation server comprises a homology comparison engine.
    - 8. A method of accessing a data manipulation server from a multi-database query system, comprising:
  - providing the query system with a query which includes a first directive assigning a value to at least one field of an input object associated with the data manipulation server and a second directive which determines a value of at least one field of an output object associated with the data manipulation server; and

invoking the data manipulation server responsive to the second directive.

- 5 10. A system according to claim 8, wherein the data manipulation server comprises a homology engine.
  - 11. A method of performing a database search using a multi-database query system, comprising:
- 10 providing the query system with a query which includes at least one directive related to a database and at least one directive related to a data manipulation server, wherein the directives are stated in an identical structural format;

translating the directives into commands recognized by the database and the data manipulation server; and

submitting the commands respectively to the data manipulation server and to the databasc.

- 12. A method according to claim 11, wherein the data manipulation server comprises a homology comparison engine.
- A method according to claim 11, wherein translating the directives comprises 13. identifying, by a query processor, the directives directed to the database and the directives directed to the data manipulation server.
- 25 14. A method according to claim 13, wherein translating the directives comprises passing the directives to translation servers associated with the database or data manipulation server to which the directives are directed.
- A method according to claim 13, comprising determining an order for the directives to be processed in and submitting the translated directives to the data manipulation server and to 30 the database according to the determined order.

Ū

- 17. A method according to claim 16, wherein translating the results into structured objects
   5 comprises translating the results to structured objects related to the directives.
  - 18. A method according to claim 11, wherein providing a query comprises providing a query in an Object Protocol Model (OPM)-like language.

entution companie

#### APPENDIX A

SCHEMA blast srv DESCRIPTION: "The OPM schema for a queryable blast server" 5 CONTROLLED VALUE CLASS BlastEngine\_Cv { "wu\_blast 2.0", "ncbi\_blast 2.0" } DEFAULT: "wu\_blast 2.0" CONTROLLED VALUE CLASS BlastProgram\_Cv 10 {"blastn", "blastx", "blastp", "tblastn", "tblastx"} DEFAULT: "blastn" CONTROLLED VALUE CLASS Strand\_Cv 15 {"top", "bottom", "both"} DEFAULT: "both" CONTROLLED VALUE CLASS SortBy\_Cv {"pvalue", "count", "highscore", "totalscore"} 20 DEFAULT: "pvalue" Ifi CONTROLLED VALUE CLASS GenCode\_Cv ij { ("Standard or Universal", 1), á ("Vertebrate Mitochondrial", 2), ("Yeast Mitochondrial", 3), ("Mold, Protozan, .. ",4), ("Invertebrate Mitochondrial", 5), ľŪ ("Ciliate Macronuclear", 6), Ē ("Encinodermate Mitochondrial",9), ("Alternative Ciliate Macronuclear", 10), ("Eubactrial", 11), ĮΠ ("Alternative Yeast", 12), Ш ("Ascidian Mitochondrial", 13), Ū ("Flatworm Mitochondrial", 14) DEFAULT: "Standard or Universal" CODE\_TYPE: SMALLINT CONTROLLED VALUE CLASS Filter\_Cv 40 { ("none", 0), ("seg", 1), ("xnu", 2), ("seg+xnu", 3), 45 ("dust", 4) DEFAULT: "none" CODE\_TYPE: SMALLINT CONTROLLED VALUE CLASS Matrix\_Cv

{ ("blosum62", 0), ("blosum35", 1), ("blosum40", 2), ("blosum40", 2), ("blosum45", 3), ("blosum50", 4), ("blosum50", 6), ("blosum70", 6), ("blosum75", 7), ("blosum80", 8), ("blosum85", 9), ("blosum85", 9), ("blosum85", 10) 5 10 ("blosum95", 10), ("blosum100"; 11), ("GONNET","12), ("GONNET","1 ("pam10","13), ("pam20", 14), ("pam30", 15), ("pam40", 16), ("pam50", 17), ("pam60", 18), ("pam70", 19), ("pam80", 20), ("pam90", 21), ("pam100", 22) 15 20 ("pam100", 22), ("pam110", 23), ("pam120", 24), ("pam130", 25), ("pam140", 26), ("pam150", 27), ("pam160"; 28); ("pam170", 29), ... ("pam180", 30); ("pam190", 31), ("pam200", 32), ("pam210", 33), ("pam220", 34), ("pam230", 35), ("pam240", 36), ("pam250", 37), ("pam260", 38), 40 ("pam270", 39), ("pam280", 40), ("pam290", 41), ("pam300", 42), ("pam310", 43), ("pam320", 44), 45 ("pam330", 45), ("pam340", 46), ("pam350", 47), ("pam360", 48), 50 ("pam370", 49),

```
086/00672
```

```
("pam380", 50),
     ("pam390", 51),
     ("pam400", 52),
     ("pam410", 53),
 5
     ("pam420", 54),
     ("pam430", 55),
      ("pam440", 56),
      ("pam450", 57)
10
     DEFAULT: "blosum62"
     CODE TYPE: SMALLINT
     CONTROLLED VALUE CLASS DB Cv
      { "testdb", "localdb", "dbest" }
15
     DEFAULT: "testdb"
     OBJECT CLASS Blast_Call
     DESCRIPTION: "A blast call object represents a particular homology search
     using a blast engine"
20
     ID: callId
     ATTRIBUTE callid: INTEGER REQUIRED
m
     ATTRIBUTE engine: BlastEngine Cv REQUIRED
     ATTRIBUTE program: BlastProgram Cv REQUIRED
Ė
     ATTRIBUTE query: VARCHAR(2000) REQUIRED
     ATTRIBUTE datasource: DB Cv REQUIRED
ATTRIBUTE output: set-of [1,] Blast Output REQUIRED
     ATTRIBUTE matrix: Matrix Cv OPTIONAL
     ATTRIBUTE strand: Strand_Cv OPTIONAL
     ATTRIBUTE sortby: SortBy_Cv OPTIONAL
     ATTRIBUTE dbgcode: GenCode_Cv OPTIONAL
     ATTRIBUTE filter: Filter_Cv OPTIONAL
     ATTRIBUTE threshold: REAL OPTIONAL
Ü
     ATTRIBUTE alignments: INTEGER OPTIONAL
     ATTRIBUTE scores: INTEGER OPTIONAL
     ATTRIBUTE param_E: REAL OPTIONAL
     ATTRIBUTE param_S: REAL OPTIONAL
     ATTRIBUTE param_E2: REAL OPTIONAL
     ATTRIBUTE param_S2: REAL OPTIONAL
     ATTRIBUTE param_W: INTEGER OPTIONAL
     ATTRIBUTE param_T: INTEGER OPTIONAL
40
     ATTRIBUTE param_X: INTEGER OPTIONAL
     ATTRIBUTE param_N: INTEGER OPTIONAL
     ATTRIBUTE param_M: INTEGER OPTIONAL
     ATTRIBUTE param B: INTEGER OPTIONAL
45
     ATTRIBUTE param_V: INTEGER OPTIONAL
     OBJECT CLASS Blast_Output
     DESCRIPTION: "The output of a specific blast call"
     ID: runId
```

50 ATTRIBUTE runid: INTEGER REQUIRED

```
ATTRIBUTE program: VARCHAR(8) REQUIRED
      ATTRIBUTE version: VARCHAR(20) REQUIRED
      ATTRIBUTE revision: VARCHAR(20) REQUIRED
      ATTRIBUTE build: VARCHAR(40) REQUIRED
     ATTRIBUTE queryId: VARCHAR(20) REQUIRED
      ATTRIBUTE querySeq: VARCHAR(2000) REQUIRED
     ATTRIBUTE queryLength: INTEGER REQUIRED
     ATTRIBUTE database : DB Cv REQUIRED
     ATTRIBUTE hits: set-of [1,] BlastHits REQUIRED
 10
     ATTRIBUTE dbSize_Seqs: INTEGER REQUIRED...
     ATTRIBUTE dbSize Letters: INTEGER REQUIRED
     ATTRIBUTE dbFile: VARCHAR(80) REQUIRED.
     ATTRIBUTE dbReleased -: VARCHAR(40) REQUIRED
     ATTRIBUTE dbPosted : VARCHAR(40) REQUIRED
15
     ATTRIBUTE bitSatE: INTEGER REQUIRED
     ATTRIBUTE searchTime: VARCHAR(40) REQUIRED
     ATTRIBUTE totalTime: VARCHAR(40) REQUIRED
     ATTRIBUTE runDate: VARCHAR(40) REQUIRED
     ATTRIBUTE parameters: set-of [1,] OutputParameters REQUIRED
20
ľ
     OBJECT CLASS OutputParameters
ID: paramId
=
     ATTRIBUTE paramid: INTEGER REQUIRED
25
     ATTRIBUTE strand: VARCHAR(10) REQUIRED
     ATTRIBUTE frame: VARCHAR(10) REQUIRED
.E
     ATTRIBUTE matrixId: VARCHAR(10) REQUIRED
     ATTRIBUTE matrixName: VARCHAR(10) REQUIRED.
F
     ATTRIBUTE lamdba_Used: VARCHAR(10) REQUIRED
30
[]
     ATTRIBUTE K Used: VARCHAR(10) REQUIRED
     ATTRIBUTE H*Used: VARCHAR(10) REQUIRED
     ATTRIBUTE lamdba_Computed: VARCHAR(10) REQUIRED.
U
     ATTRIBUTE K...Computed: VARCHAR(10) REQUIRED
Ū,
     ATTRIBUTE H Computed: VARCHAR(10) REQUIRED
     ATTRIBUTE param E1: VARCHAR(10) REQUIRED
     ATTRIBUTE param_S1: VARCHAR(10) REQUIRED
     ATTRIBUTE param_WI: VARCHAR(10) REQUIRED
     ATTRIBUTE param_T1: VARCHAR(10) REQUIRED
     ATTRIBUTE param X1: VARCHAR(10) REQUIRED
40
     ATTRIBUTE param_E2: VARCHAR(10) REQUIRED
     ATTRIBUTE param_S2: VARCHAR(10) REQUIRED
     OBJECT CLASS BlastHeader
     DESCRIPTION: "The header section of BLAST output"
45
     ID: headerId
     ATTRIBUTE headerid: INTEGER REQUIRED
     ATTRIBUTE program: VARCHAR(8) REQUIRED
     ATTRIBUTE version: VARCHAR(20) REQUIRED
     ATTRIBUTE revision: VARCHAR(20) REQUIRED
```

ATTRIBUTE build: VARCHAR(40) REQUIRED

086/00672



ATTRIBUTE queryId: VARCHAR(20) REQUIRED
ATTRIBUTE querySeq: VARCHAR(2000) REQUIRED

ATTRIBUTE database : DB\_Cv REQUIRED

ATTRIBUTE numOfSequences: INTEGER REQUIRED
5 ATTRIBUTE numOfLetters: INTEGER REQUIRED

OBJECT CLASS BlastHits DESCRIPTION: "Blast Hits"

ID: accession

10 ATTRIBUTE accession: VARCHAR(12) REQUIRED
ATTRIBUTE description: VARCHAR(255) REQUIRED
ATTRIBUTE score: INTEGER REQUIRED

ATTRIBUTE score: INTEGER REQUIRED
ATTRIBUTE pvalue: REAL REQUIRED
ATTRIBUTE num: INTEGER REQUIRED
ATTRIBUTE length: INTEGER OPTIONAL

15 ATTRIBUTE length: INTEGER OPTIONAL ATTRIBUTE hsp: set-of[1,] BlastHSP OPTIONAL

#### **OBJECT CLASS BlastHSP**

ID: hspId

ıD

ATTRIBUTE hspld: INTEGER REQUIRED
ATTRIBUTE score: INTEGER REQUIRED
ATTRIBUTE expect: REAL REQUIRED
ATTRIBUTE pvalue: REAL REQUIRED

ATTRIBUTE strand1: VARCHAR(1) REQUIRED
ATTRIBUTE strand2: VARCHAR(1) REQUIRED
ATTRIBUTE identities: REAL REQUIRED
ATTRIBUTE positives: REAL REQUIRED
ATTRIBUTE query (sequence, begin, end):

(VARCHAR(500) REQUIRED, INTEGER REQUIRED, INTEGER REQUIRED)

ATTRIBUTE target (sequence, begin, end):

(VARCHAR(500) REQUIRED, INTE

ATTRIBUTE align: VARCHAR(500) PEO

(VARCHAR(500) REQUIRED, INTEGER REQUIRED, INTEGER REQUIRED)

ATTRIBUTE align: VARCHAR(500) REQUIRED ATTRIBUTE to begin: INTEGER REQUIRED ATTRIBUTE to end: INTEGER REQUIRED

